

**Power USB-C Double Socket PD/QC without LED**

Art. No. 67371050 (BP)

Art. No. 67371550 (SP)

24.07.2024

Input voltage: 8 - 30 V DC

Output USB-C1:

Input Voltage	Output voltage	Output current max.
12,0V	5,0V	3,0A
	9,0V	3,0A
	12,0V	2,5A
24,0V	5,0V	3,0A
	9,0V	3,0A
	12,0V	2,5A
	15,0V	2,0A
	20,0V	1,5A

Output USB-C2:

Input Voltage	Output voltage	Output current max.
12,0V	5,0V	3,0A
	9,0V	3,0A
	12,0V	2,5A
24,0V	5,0V	3,0A
	9,0V	3,0A
	12,0V	2,5A
	15,0V	2,0A
	20,0V	1,5A

## **Power USB-C Double Socket PD/QC without LED**

Art. No. 67371050 (BP)

Art. No. 67371550 (SP)

24.07.2024

USB-C1 and USB-C2 outputs are independent of each other, they can be used individually or together.

Output power according to PD and QC protocol:

USB-C 1,2 (PD):	30 W each
Output power max.:	2 x 30 W
Charging protocol C-socket:	Power Delivery (PD), Quick Charge, PPS
Current consumption:	max. 5 mA (idle)
Protection against:	short circuit, overload, overvoltage, reverse polarity and overtemperature

Panel thickness:	from 2 mm to 16 mm
------------------	--------------------

Mounting hole:	28 mm (27,8mm)
----------------	----------------

### **Material:**

Housing:	Makrolon
----------	----------

Temperature load:	max. 130 °C
-------------------	-------------

### **Cable:**

Stranded cable:	2 x 0,5 mm <sup>2</sup> red (+) / black (-)
-----------------	---

Length:	150 mm
---------	--------

**Power USB-C Double Socket PD/QC without LED**

Art. No. 67371050 (BP)

Art. No. 67371550 (SP)

24.07.2024

